



DFRB-045-E

desiccant rotor air dehumidifier




technical data

Process/Dry Air Flow	450/350	m ³ /h
Available Pressure For Ducting	150	Pa
Reactivation Air Flow	100	m ³ /h
Available Pressure For Ducting	50	Pa
Nominal Drying Capacity (*)	1,9	kg/h
Total Power Supply	2,5	Kw
Motors Power	0,4	Kw
Reactivation Heater Power	2,1 (nominal) 2,4 (maxim)	Kw
Electrical Supply	230V//50Hz	

09/04 F-1537-01/B

(*) Nominal capacity: 20°C and 60% R.H.

capacity diagram (*)



Settled Parameters:

- Process/Reactivation Air Temperature: 20 °C
- ΔT Reactivation Heater According To Nominal Power
- Equal Process/Reactivation Air Moisture Content

(*) At other operating conditions, pls. ask for the corresponding performances




specification

Air dehumidifier by high performance desiccant silicagel rotary element, brand FISAIR, model DFRB-045-E:

- Self-supporting stainless steel sheet housing, easily serviceable, with top handle for carriage.
- Air intake with G3 filter mat, centrifugal simple ear air fan with direct motor drive.
- Rotary desiccant element driven by gear motor, teeth pulley and transmission belt, with three front sections; for dry, heat recovery and wet air streams.
- Partition and peripheral contact-type airseals.
- Dessicant reactivation air heater PTC-type, with self limited operation temperature.
- Process inlet, dry and wet outlets; with round connectors with rubber seals.
- Two meters long connection cable with socket. On-off switch with on-light.
- Operation Ampere gage.
- Performance, airflows and other data as per front page.

overall dimensions



Remark: - Approx. weight: 35 kg
- All dimensions in mm